

# e.sybox mini<sup>3</sup>

**ONE OF A KIND**

## CONSTANT PRESSURE

### FOR MAXIMUM COMFORT

Thanks to inverter technology, once you have set the desired pressure, e.sybox mini3 maintains a constant pressure to all the water outlets served.

## INTEGRATED

### ALL IN ONE

With the exception of the suction and delivery pipes, it doesn't require any additional components for installation.

## SILENT OPERATION

### DESIGNED FOR RELAXATION

**QUIET**  
45 dB (A)\*

\*duty point 10 l/m at 2.7 bar at 1m

## DISPLAY

### EASY ADJUSTMENT

LCD 70X40 high-resolution screen, adjustable to adapt readability at various installations. The intuitive interface gives access to all the information and to customise the main settings depending on the application.

## APPLICATIONS

### EASY ADJUSTMENT

Apartments up to 3 floors, 2 bathrooms and 50m<sup>2</sup> of garden



**ANTI-FREEZE PROTECTION**



## TECHNICAL DATA

### OPERATING RANGE:

Flow rate up to 80l/min; head up to 55m

### PUMPED LIQUID:

Clean, free from solids or abrasive substances, non viscous, non aggressive, non crystallised and chemically neutral

### LIQUID TEMPERATURE RANGE:

From 0°C to + 35°C for domestic use and

From 0°C + 40°C for other uses

**MAXIMUM SUCTION DEPTH:** 8 metres

**MAXIMUM AMBIENT TEMPERATURE:** +50°C

**MAXIMUM WORKING PRESSURE:** 7.5 bar (750 kPa)

**MOTOR PROTECTION:** IPX4

**INSULATION CLASS:** F



**DAB-ESYBOXMINI<sup>3</sup> - 805406**

**2019**