



- 01 **Save time:** Manage from anywhere around the world
- 02 **Save money:** Avoid costly on-site visits by making schedule changes from anywhere
- 03 **Predictive Watering™ adjustments:** Integrate local weather data to make water-saving scheduling adjustments

 **Hydrawise® Ready**

PRO-HC OUTDOOR PROFESSIONAL-GRADE WI-FI CONTROLLER WITH HYDRAWISE WEB-BASED SOFTWARE

Manage your Pro-HC irrigation controller from anywhere worldwide using your smart device or web browser with Hydrowise cloud software. Predictive Watering adjusts schedules based on temperature forecast, rainfall probability, wind speed, and humidity to provide maximum water savings while keeping landscapes healthy and beautiful. Add a simple-to-install flow meter and set up automatic notifications to alert you of broken pipes or sprinklers.

Hydrawise cloud software is a user-friendly water management tool. Homeowners can use Predictive Watering adjustments to lower their water bills. Hydrowise software enables professional contractors to conduct in-depth water management while monitoring the piping and electrical systems. The professional cloud-based irrigation software works for everyone!

The Pro-HC controller is Smart WaterMark approved when connected to Hydrowise web-based software.



Try Hydrowise today!
Visit hydrowise.com

Learn more. Visit hunterindustries.com or contact your local sales manager.

PRO-HC CONTROLLER FEATURES & SPECIFICATIONS

Key Benefits

- Easy-to-use touchscreen interface
- Wi-Fi enabled for simple and fast connection to the internet
- 6-, 12-, and 24-station fixed models
- Dedicated master valve/pump start
- Large terminal strips
- Built-in milliamp sensor
- 2 sensor ports
- Warranty: 2 years

Models



Plastic Indoor
Height: 21 cm
Width: 24 cm
Depth: 8.8 cm



Plastic Outdoor
Height: 22.8 cm
Width: 25 cm
Depth: 10 cm



HC Flow Meter - 3/4"
(20 mm) MBSP thread
Height: 8 cm
Length: 23.2 cm
Depth: 8 cm

HC Flow Meter - 1/2"
(40 mm) MBSP thread
Height: 16.2 cm
Length: 43.1 cm
Depth: 12.5 cm

HC Flow Meter - 1"
(25 mm) MBSP thread
Height: 9.3 cm
Length: 26.2 cm
Depth: 8 cm

HC Flow Meter - 2"
(50 mm) MBSP thread
Height: 16.2 cm
Length: 44.7 cm
Depth: 12.5 cm

PRO-HC - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Transformer	3 Indoor/Outdoor	4 Options
PHC-6 = 6-station controller PHC-12 = 12-station controller PHC-24 = 24-station controller	00 = 120 VAC 01 = 230 VAC	(blank) = Outdoor model (internal transformer) i = Indoor model (plug-in transformer)	(blank) = No option E = 230 VAC with European connections A = 230 VAC with Australian connections (outdoor model has internal transformer with cord)

Example:

PHC-2400 = 24-station, 120 VAC, outdoor plastic controller

Advanced Features

- **Predictive Watering Adjustments:** Daily schedule adjustments (based on local weather data) monitor past, current, and forecast temperature, rainfall, humidity, and wind speed. This allows for adjustments of watering times and schedules to balance water savings with water efficiency for plants.
- **Wiring Detection and Alerts:** The Pro-HC controller continuously monitors the electrical current flowing to solenoid valves. If the current is too high or too low, Hydrowise will alert you and tell you which valve is not working properly. This allows you to fix a faulty valve before damage is done to the landscape.
- **Advanced Sensor Ports:** Two general-purpose sensor ports can be used for many different functions. Sensor ports work with Hunter HC Flow Meters for flow monitoring and alerts, as well as Hunter Klik and standard rain and soil sensors to stop irrigation. The sensor ports can also start an irrigation cycle. This allows you to create custom starts based on sensor readings.
- **Built to Last:** The Pro-HC features a double-door design, which makes it extremely durable in all weather conditions. It also includes large terminal strips for easy installation of solenoid wiring.

HC FLOW METER - OPTIONS

Models	Description
HC-075-FLOW	HC Flow Meter with 3/4" (20 mm) MNPT thread
HC-100-FLOW	HC Flow Meter with 1" (25 mm) MNPT thread
HC-150-FLOW	HC Flow Meter with 1 1/2" (40 mm) MNPT thread
HC-200-FLOW	HC Flow Meter with 2" (50 mm) MNPT thread
HC-075-FLOW-B	HC Flow Meter with 20 mm MBSP thread
HC-100-FLOW-B	HC Flow Meter with 25 mm MBSP thread
HC-150-FLOW-B	HC Flow Meter with 40 mm MBSP thread
HC-200-FLOW-B	HC Flow Meter with 50 mm MBSP thread

Website hunterindustries.com | **Customer Support** +1 760-752-6037 | **Technical Service** +1 760-591-7383 support@hydrowise.com

Helping our customers succeed is what drives us. While our passion for innovation and engineering is built into everything we do, it is our commitment to exceptional support that we hope will keep you in the Hunter family of customers for years to come.



Gene Smith

Gene Smith, President, Landscape Irrigation and Outdoor Lighting