Filters



Filtration devices designed to trap foreign particles in the water and reduce risk of clogging of emitters.

Features

- In-Line model with barbed inlet and outlet.
- Snap-On model for direct connection to standard tap adaptors.
- 80 mesh screen filter.
- Easily taken apart for cleaning.
- Effective compact filters with minimal flow losses.

Applications

For low pressure micro irrigation systems.



Ordering Information - In-line Filters 80 mesh Screen

Туре	Order Code	Pack Quantity	Packs per Carton	Carton (kg)
In-Line Filter 13 mm barb	44355	25	14	10.9
In-Line Filter 14 mm barb	44395	25	14	10.2
In-Line Filter 16 mm barb	44365	25	12	9.9
In-Line Filter 19 mm barb	44375	25	6	7.4
In-Line Filter 25 mm barb	44445	10	8	7.0

Ordering Information - Snap-On Filters 80 mesh Screen

19 mm

40 mm

43 g

Туре	Order Code	Pack Quantity	Packs per Carton	Carton (kg)
Snap-On Filter 13 mm barb	44405	25	10	9.5
Snap-On Filter 14 mm barb	44435	25	10	9.5
Snap-On Filter 16 mm barb	44415	25	10	9.6
Snap-On Filter 19 mm barb	44425	25	6	8.5

Material

acetal Inlet

TPE

HDPE

polyproplene

TAIL Inlet

WASHER

SCREEN

BODY & NUT

Base/Connection type

Outlet Barb 13, 14, 16, 19 mm

Barb 13, 14, 16, 19 mm

In-Line Filter

Snap-On Filter Specifications - In-Line Filter

13, 14

16 mm

33 mm

28 g

132 mm | 175 mm

Dimensions

Assembled

WEIGHT (approx.)

LENGTH

WIDTH



Assembled	16 mm					, , , , , , , , , , , , , , , , , , , ,
LENGTH	134 mm	175 mm	BODY Snap-On	Inlet acetal	Inlet	Snap-On Connector
WIDTH	33 mm	40 mm	SLEEVE	polyproplene	Outlet	Barb 13, 14, 16,19 mm
WEIGHT (approx.)	35 g	51 g	BODY & NUT	polyproplene		
			WASHER	TPE		
			SCREEN	HDPE		

Specifications - Snap-On Filter

Dimensions Assembled	13, 14 16 mm	19 mm	Material			Base	e/Connection Type
LENGTH	134 mm	175 mm	BODY Snap-On	Inlet ace	etal	Inlet	Snap-On Connector
WIDTH	33 mm	40 mm	SLEEVE	polyprople	ene	Outlet	Barb 13, 14, 16,19 mm
WEIGHT (approx.)	35 g	51 g	BODY & NUT	polyprople	ene		
			WASHER	T	TPE		
			SCREEN	HD	OPE		



In-Line Filter cut away detail

In-Line Filter 25 mm